

Pre-MOTD MINI Prep Checklist

- □ Oil Close to 5K mark on current Oil? Go for an early change.
- Under Bonnet Check –Look for leaks, broken/worn engine mounts, worn plug wires
- □ Gearbox Oil If near 2 years or 50K miles Change
- □ Brakes Check Rotors and Pads Have at least 50% left
- □ Brake Fluid If near 1 year or 25K miles Change
- Coolant MINI recommends every 4 years from build date for a change, every 2 years would not hurt.
- □ Tires Tread level should be at least ½, check for uneven wear
- □ Wheels Check Torque on lugs 83ft/lb 1st gen, 102ft/lb 2nd gen Check often on site. See Chad at

Detroit Tuned tent to use his torque wrench.

- □ Wipers Replace blades if older It could be quite wet at MOTD
- Lights Check all lights to verify operation
- □ Battery good condition, make sure is securely fastened
- □ Suspension Check all bushings for wear, replace as needed
- □ Steering Check for wear replace anything questionable
- □ Exhaust Secure with no leaks, check mounts
- □ Wheel Bearings Check for excessive play

Running The Dragon even at the posted limit taxes all the systems on our MINIs. 311 Turns in rapid succession will find the weaknesses if not attended to ahead of time. Please be sure to check you braking system well.

Check list compiled with the assistance of Chad from **Detroit Tuned**.